

Punt

300,301,303



PUNT 300, 301, AND 303 ARE AUTOMATIC MACHINES FOR SPREADING TUBULAR FABRIC, BUILT UNDER SPECIAL CHARACTERISTICS, WITH WHICH WE ACHIEVE THE BEST PAVING QUALITIES ON THE MARKET.



Punt

300,301,303



TECHNICAL CHARACTERISTICS	PUNT 300	PUNT301	PUNT 303
Equipped with Robotic Technology	Yes	Yes	Yes
Spread without tension	Yes	Yes	Yes
Automatic feed roll	No	Yes	Yes
Automatic double feeder	No	Yes	Yes
Automatic check control	Yes	Yes	Yes
Speed up to 100m/min.	Yes	Yes	Yes
Automatic spread height detector	Yes	Yes	Yes
Machine driven by four wheels	No	Yes	Yes
Control Desk with digital touch screen	Yes	Yes	Yes
Speed adjustable	No	Yes	Yes
Brakes by tension cutting	Yes	Yes	Yes
Fitted with modem for technical assistance on-line	Yes	Yes	Yes
Roll support for rollers	No	Yes	Yes
Highlight screen to check the task	Optional	Optional	Yes
4 sets of stretchers from 23 to 120cm	Yes	Yes	Yes
Connection to network	No	Yes	Yes
Quarterturn equipment	No	Optional	Yes
Adjustable size of the stretchers	No	Optional	Yes
Quarterturn adjustable	No	Optional	Yes

OPTIONS

Extra Stretcher for quarterturn	No	Optional	Yes
Double feeder for book folded	No	Optional	Optional
Intelligent control handle	Optional	Optional	Optional
Program to count meters per roll, Working time and total meters spread	No	Yes	Yes
On Line Autex.com to program automatically the faults and spreading meters	No	No	Yes
Smooth, air-blowing tables and conveyors	Yes	Yes	Yes
Transfer table	Yes	Yes	Yes
Operators platform	Yes	Yes	Yes
Special tables on request	Yes	Yes	Yes
Quarterturn equipment on the operators side	Optional	Optional	Optional



C/ Can Negoci, 18 - P.I. Can Negoci
08310 Argentona - Barcelona - Spain
Teléfono: 0034 93 7589325
ventas@autex-int.com
www.autex-int.com

